IGBT - Power, Single, N-Channel, Field Stop VII (FS7), SCR, Power TO247-3L

1200 V, 1.4 V, 25 A

AFGHL25T120RW

BV_{CES}	$V_{CE(sat)}$ TYP	I_C MAX
1200 V	1.4 V	25 A





TO−247−3LD
CASE 340CX

Description

Using the novel field stop 7th generation IGBT technology in TO247 3−lead package, this device offers the optimum performance with low on state voltage and minimal switching losses for both hard and soft switching topologies in automotive applications.

Features

- Extremely Efficient Trench with Field Stop Technology
- Maximum Junction Temperature − T_J = 175°C
- Short Circuit Rated and Low Saturation Voltage
- Fast Switching and Tightened Parameter Distribution
- AEC−Q101 Qualified, PPAP Available Upon Request
- This Device is Pb−Free, Halogen Free/BFR Free and is RoHS Compliant

Applications

- Automotive E−compressor
- Automotive EV PTC Heater
- OBC

MARKING DIAGRAM



AFGH25120RW = Specific Device Code
&Z = Assembly Plant Code
&3 = 3−Digit Date Code
&K = 2−Digit Lot Traceability Code
$Y = **onsemi** Logo

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Collector−to−Emitter Voltage		V_{CE}	1200	V
Gate−to−Emitter Voltage		V_{GE}	±20	
Transient Gate−to−Emitter Voltage			±30	
Collector Current	T_C = 25°C	I_C	50	A
	T_C = 100°C		25	
Power Dissipation	T_C = 25°C	P_D	468	W
	T_C = 100°C		234	
Pulsed Collector Current	T_C = 25°C, t_p = 10 μs (Note 1)	I_{CM}	75	A
Short Circuit Withstand Time V_{GE} = 15 V, V_{CC} = 800 V, T_C = 150°C		T_{SC}	6	μs
Operating Junction and Storage Temperature Range		T_J, T_{stg}	−55 to +175	°C
Lead Temperature for Soldering Purposes		T_L	260	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Repetitive rating: Pulse width limited by max. junction temperature

ORDERING INFORMATION

Device	Package	Shipping
AFGHL25T120RW	TO−247−3L (Pb−Free)	30 Units / Tube

© Semiconductor Components Industries, LLC, 2023

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case IGBT	$R_{\theta JC}$	0.32	°C/W
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	40	°C/W

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−to−Emitter Breakdown Voltage	BV_{CES}	V_{GE} = 0 V, I_C = 1 mA	1200	–	–	V
Zero Gate Voltage Collector Current	I_{CES}	V_{GE} = 0 V, V_{CE} = V_{CES}	–	–	40	μA
Gate−to−Emitter Leakage Current	I_{GES}	V_{GE} = ±20 V, V_{CE} = 0 V	–	–	±400	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GE(th)}$	V_{GE} = V_{CE}, I_C = 25 mA, T_J = 25°C	5.1	6.0	6.9	V
Gate−to−Emitter Saturation Voltage	$V_{CE(sat)}$	V_{GE} = 15 V, I_C = 25 A, T_J = 25°C	–	1.4	1.73	V
		V_{GE} = 15 V, I_C = 25 A, T_J = 175°C	–	1.62	–	
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{IES}	V_{CE} = 30 V, V_{GE} = 0 V, f = 1 MHz	–	3057	–	pF
Output Capacitance	C_{OES}		–	94.2	–	
Reverse Transfer Capacitance	C_{RES}		–	16.2	–	
Total Gate Charge	Q_G	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 25 A	–	113	–	nC
Gate−to−Emitter Charge	Q_{GE}		–	27.2	–	
Gate−to−Collector Charge	Q_{GC}		–	50	–	
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD (Note: Si Diode Applied)						
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 0/15 V, I_C = 12.5 A, R_G = 4.7 Ω, T_J = 25°C	–	33.8	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	223	–	
Rise Time	t_r		–	19.7	–	
Fall Time	t_f		–	192	–	
Turn−On Switching Loss	E_{on}		–	0.55	–	mJ
Turn−Off Switching Loss	E_{off}		–	0.86	–	
Total Switching Loss	E_{ts}		–	1.41	–	
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 0/15 V, I_C = 25 A, R_G = 4.7 Ω, T_J = 25°C	–	36.9	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	175	–	
Rise time	t_r		–	35.4	–	
Fall Time	t_f		–	126	–	
Turn−On Switching Loss	E_{on}		–	1.57	–	mJ
Turn−Off Switching Loss	E_{off}		–	1.06	–	
Total Switching Loss	E_{ts}		–	2.62	–	

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD (Note: Si Diode Applied)						
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 0/15 V, I_C = 12.5 A, R_G = 4.7 Ω, T_J = 175°C	–	37.7	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	315	–	
Rise Time	t_r		–	27.1	–	
Fall Time	t_f		–	384	–	
Turn−On Switching Loss	E_{on}		–	0.78	–	mJ
Turn−Off Switching Loss	E_{off}		–	1.6	–	
Total Switching Loss	E_{ts}		–	2.38	–	
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 0/15 V, I_C = 25 A, R_G = 4.7 Ω, T_J = 175°C	–	42.2	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	235	–	
Rise time	t_r		–	46.5	–	
Fall Time	t_f		–	242	–	
Turn−On Switching Loss	E_{on}		–	2.23	–	mJ
Turn−Off Switching Loss	E_{off}		–	1.9	–	
Total Switching Loss	E_{ts}		–	4.14	–	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 1. Output Characteristics



Figure 2. Output Characteristics



Figure 3. Output Characteristics



Figure 4. Transfer Characteristics



Figure 5. Saturation Characteristics



Figure 6. Saturation Voltage vs. Junction Temperature

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 7. Capacitance Characteristics



Figure 8. Gate Charge Characteristics



Figure 9. Switching Time vs Gate Resistance



Figure 10. Switching Time vs Gate Resistance



Figure 11. Switching Loss vs Gate Resistance



Figure 12. Switching Loss vs Gate Resistance

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 13. Switching Time vs Collector Current



Figure 14. Switching Time vs Collector Current



Figure 15. Switching Loss vs Collector Current



Figure 16. Switching Loss vs Collector Current



Figure 17. Transient Thermal Impedance of IGBT

Share Feedback
Your Opinion Matters

TO−247−3LD
CASE 340CX
ISSUE A

DATE 06 JUL 2020





NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.40	1.50	1.60
D	20.32	20.57	20.82
E	15.37	15.62	15.87
E2	4.96	5.08	5.20
e	~	5.56	~
L	19.75	20.00	20.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
Q	5.34	5.46	5.58
S	5.34	5.46	5.58
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D1	13.08	~	~
D2	0.51	0.93	1.35
E1	12.81	~	~
ØP1	6.60	6.80	7.00

GENERIC MARKING DIAGRAM*

XXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot " ▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON93302G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO−247−3LD	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales